



## TUBES INOX

### TUBES SOUDÉS CORROSION "ASTM"

POUCES	SCHEDULE	DIMENSIONS mm	NF EN 10088-1		MASSE LINÉIQUE kg/m
			1.4307 (AISI 304 L)	1.4404 (AISI316 L)	
1/8"	10 S	10,29 x 1,24	●	●	0,282
	40 S	10,29 x 1,73	●	●	0,372
1/4"	10 S	13,72 x 1,65	●	●	0,501
	40 S	13,72 x 2,24	●	●	0,646
3/8"	10 S	17,15 x 1,65	●	●	0,643
	40 S	17,15 x 2,31	●	●	0,862
1/2"	5 S	21,34 x 1,65	●	●	0,817
	10 S	21,34 x 2,11	●	●	1,020
	40 S	21,34 x 2,77	●	●	1,293
3/4"	5 S	26,67 x 1,65	●	●	1,038
	10 S	26,67 x 2,11	●	●	1,302
	40 S	26,67 x 2,87	●	●	1,717
1"	5 S	33,40 x 1,65	●	●	1,317
	10 S	33,40 x 2,77	●	●	2,132
	40 S	33,40 x 3,38	●	●	2,550
1"1/4	5 S	42,16 x 1,65	●	●	1,680
	10 S	42,16 x 2,77	●	●	2,742
	40 S	42,16 x 3,56	●	●	3,454
1"1/2	5 S	48,26 x 1,65	●	●	1,933
	10 S	48,26 x 2,77	●	●	3,167
	40 S	48,26 x 3,68	●	●	4,123
2"	5 S	60,33 x 1,65	●	●	2,433
	10 S	60,33 x 2,77	●	●	4,007
	40 S	60,33 x 3,91	●	●	5,544
2"1/2	5 S	73,03 x 2,11	●	●	3,761
	10 S	73,03 x 3,05	●	●	5,364
	40 S	73,03 x 5,16	●	●	8,802
3"	5 S	88,90 x 2,11	●	●	4,602
	10 S	88,90 x 3,05	●	●	6,581
	40 S	88,90 x 5,49	●	●	11,509
3"1/2	5 S	101,6 x 2,11			5,276
	10 S	101,6 x 3,05			7,554
	40 S	101,6 x 5,74			13,829
4"	5 S	114,3 x 2,11	●	●	5,949
	10 S	114,3 x 3,05	●	●	8,528
	40 S	114,3 x 6,02	●	●	16,383



## TUBES INOX

### TUBES SOUDÉS CORROSION "ASTM"

POUCES	SCHEDULE	DIMENSIONS mm	NF EN 10088-1		MASSE LINÉIQUE kg/m
			1.4307(AISI 304 L)	1.4404(AISI 316 L)	
5"	5 S	141,3 x 2,77	●	●	9,644
	10 S	141,3 x 3,40	●	●	11,784
	40 S	141,3 x 6,55	●	●	22,183
6"	5 S	168,28 x 2,77	●	●	11,522
	10 S	168,28 x 3,40	●	●	14,089
	40 S	168,28 x 7,11	●	●	28,800
8"	5 S	219,1 x 2,77	●	●	15,060
	10 S	219,1 x 3,76	●	●	20,349
	40 S	219,1 x 8,18	●	●	43,362
10"	5 S	273 x 3,40	●	●	23,038
	10 S	273 x 4,19	●	●	28,307
	40 S	273 x 9,27	●	●	61,444
12"	5 S	323,85 x 3,96	●	●	31,837
	10 S	323,85 x 4,57	●	●	36,672
	40 S	323,85 x 9,53	●	●	75,285
14"	5 S	355,6 x 3,96	●	●	34,997
	10 S	355,6 x 4,78	●	●	42,146
	40 S	355,6 x 9,53	●	●	82,889
16"	5 S	406,4 x 4,19	●	●	42,355
	10 S	406,4 x 4,78	●	●	48,249
	40 S	406,4 x 9,53	●	●	95,057
18"	5 S	457,2 x 4,19	●	●	47,705
	10 S	457,2 x 4,78	●	●	54,351
	40 S	457,2 x 9,53	●	●	107,224
20"	5 S	508,0 x 4,78	●	●	60,454
	10 S	508,0 x 5,54	●	●	69,960
	40 S	508,0 x 9,53	●	●	119,391
24"	5 S	609,6 x 5,54	●	●	84,107
	10 S	609,6 x 6,35	●	●	96,275
	40 S	609,6 x 9,53	●	●	143,726

Soudure TIG

Hypertrempés

Fabrication selon ASTM A 312

Longueur courante : 6 mètres (pas de coupe)

● STOCK PERMANENT  
AUTRES DIMENSIONS, NOUS CONSULTER