

Technical data sheet

Hooked-end steel fibres

HE 90/60

Dimensions

Wire diameter (d)	0.90 mm (± 0.04 mm)
Fibre length (L)	60.0 mm (+2/-3 mm)
Hook length (l and l')	1 – 4
Hook depth (h and h')	1.80 mm (+1/-0 mm)
Bending angle (α and α')	45° (min. 30°)
Aspect ratio (L/d)	67
Camber of the fibre	max. 5% of L'
Torsion angle of the fibre	< 30°
Number of fibres per kg	3200
Total fibre length per 10 kg	1920 m

Packaging

Recyclable cardboard boxes	
Net weight/box	25 kg
Boxes/palette	48
Weight/palette	1200 kg
The fibres are oriented in one direction	
Palettes are wrapped or welded in a plastic folio	
Available also in big bag of 500 kg	

Miscellaneous

The described fibre is in accordance with the following standards:

- EN 14889-1 type 1 (cold-drawn wire),
- ASTM A820/A820M-04 type 1 (cold-drawn wire).

All information in this promotional material illustrates products and services in a non final way and invites further technical or commercial explanation. This is not contractual. Copyright ArcelorMittal – June 2011.

Material characteristics

- Tensile strength of drawn wire
1200 N/mm²

