



## RACCORD INOX

### BRIDES PLEINES (TYPE O5)

Nuances selon NF EN 10088-1 : 1.4307 (AISI 304L) et 1.4404 (AISI 316 L)

### BRIDES ISO PN10

DN mm	DIMENSIONS			BOULONNERIE		C4 mm	G mm
	D	K mm	L mm	Nbre trous	Ø mm		
10 à 150	Il n'existe pas de brides PN10 dans cette gamme de DN. Prendre les brides ISO PN16 (voir ci-dessous)						
200	340	295	22	8	M 20	24	190
250	395	350	22	12	M 20	26	240
300	445	400	22	12	M 20	26	290
350	505	460	22	16	M 20	26	325
400	565	515	26	16	M 24	28	375
450	615	565	26	20	M 24	28	425
500	670	620	26	20	M 24	30	475
600	780	725	30	20	M 27	34	575

### BRIDES ISO PN16

DN mm	DIMENSIONS			BOULONNERIE		C4 mm	G mm
	D	K mm	L mm	Nbre trous	Ø mm		
10	90	60	14	4	M 12	14	
15	95	65	14	4	M 12	14	
20	105	75	14	4	M 12	16	
25	115	85	14	4	M 12	16	
32	140	100	18	4	M 16	18	
40	150	110	18	4	M 16	18	
50	165	125	18	4	M 16	18	
65	185	145	18	4	M 16	20	55
80	200	160	18	8	M 16	20	70
100	220	180	18	8	M 16	22	90
125	250	210	18	8	M 16	22	115
150	285	240	22	8	M 20	24	140
200	340	295	22	12	M 20	26	190
250	405	355	26	12	M 24	26	240
300	460	410	26	12	M 24	28	290
350	520	470	26	16	M 24	30	325
400	580	525	30	16	M 27	32	375
450	640	585	30	20	M 27	36	425
500	715	650	33	20	M 30	40	475
600	840	770	36	20	M 33	44	575

Fabrication et dimensions selon NF E 29-203

SUR DEMANDE JUSQU'À PN 100, NOUS CONSULTER

